

PVC Vacuum Flexible Ducting





Flexible PVC hose with galvanised steel spiral with polyester yarn reinforcement, for suction and transport of liquids and dusts.

SMOOTH SURFACES	***
FLEXIBILITY	***
ABRASION RESIST ANCE	***
TEMPERATURE RANGE	-5°C +65°C 23°F +149°F
CHEMICAL RESIST ANCE	PVC table
CRUSHING RESIST ANCE	***

CONSTRUCTION:

Plasticised PVC with encapsulated axial and helical re-inforcing yarns supported by a PVC covered spring steel helix.

COLOUR:

Black with white yarns.

STANDARD LENGTH:

15 Metre lengths up to and including 63mm diameter 10 Metre lengths 70mm diameter and above.

APPLICATIONS:

Air handling, dust and fume extraction. Particularly suitable for domestic and industrial vacuum cleaners.

PROPERTIES

Flexible, smooth bore ducting. Robust and easy to handle with good abrasion resistance.

Diameter mm	Weight Kg/M	Bend Radius mm	Working Pressure Bar	Working Vacuum Bar
25	0.22	25	1.05	0.91
32	0.27	32	1.00	0.91
35	0.34	35	1.00	0.85
38	0.37	38	0.95	0.80
41	0.40	41	0.95	0.75
44	0.43	44	0.90	0.70
51	0.49	51	0.90	0.59
64	0.61	64	0.80	0.43
70	0.77	70	0.75	0.40
76	0.85	76	0.95	0.50
80	0.90	80	0.95	0.45