



DUST SPARES

dust control spare parts for industry
www.dustspares.co.uk

Tel: 08456 800 696
Fax: 08456 800 699
Email: info@dustspares.co.uk

WYREFLEX

Double Ply Neoprene Coated Ducting

Construction:

Double ply, Neoprene coated polyester fabric flexible ducting complete with twin steel wire helix.

Colour:

Black with yellow identification strip from 76mm.

Standard Length:

4m length.

Temperature Range:

-55°C to +130°C

Applications:

Suitable for suction and conveyance of air, fumes and gases. Dust collection and light materials handling.

Properties:

Excellent flexibility permits a tight bend radius without kinking.



Double Ply Neoprene Coated Ducting

Diameter mm	Weight Kg/M	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
25	0.30	45	0.70	0.35
32	0.40	45	0.70	0.30
38	0.40	45	0.70	0.30
44	0.40	60	0.65	0.30
51	0.50	60	0.65	0.30
57	0.60	70	0.60	0.25
64	0.70	70	0.60	0.25
70	0.70	95	0.60	0.20
76	0.70	95	0.50	0.20
83	0.90	110	0.50	0.20
89	0.90	110	0.50	0.20
102	1.30	120	0.50	0.15
114	1.50	120	0.45	0.15
127	1.70	145	0.45	0.10
140	1.90	175	0.45	0.10
152	2.10	175	0.35	0.10
178	2.40	220	0.35	0.05
203	3.20	240	0.30	0.05
229	3.60	270	0.20	0.05
254	4.40	290	0.20	0.05
305	6.40	340	0.10	0.02

Technical data at +20°C