



**DUST SPARES**  
dust control spare parts for industry

Tel: 08456 800 696  
Fax: 08456 800 699  
Email: info@dustspares.co.uk

[www.dustspares.co.uk](http://www.dustspares.co.uk)

## **PE350 Checkstat & Oleophobic**

Fibre Composition: 100% Polyester

Scrim Composition: 100% Stainless Steel

Surface Finish: Glazed

Chemical Treatment: Oleophobic Chemical treatment

Weight: 350g/m<sup>2</sup>

Thickness: 1.4 mm

Air Permeability: 290 dm<sup>3</sup>/dm<sup>2</sup>/min @ 200mm WG

Maximum Temperature: 150 0C (continuous)

Maximum Temperature 170 0C (surge)

Good resistance to a majority of mineral and organic acids

Moderate resistance to alkalis

Moderate resistance to hydrolysis

Oil and water Repellent

Typical Electrical Resistance values (Ohms) with the test apparatus type used for DIN 54345 Part 5

<b>Polyester</b>	<b>2.5% Stainless Steel with Stainless Steel conductive scrim</b>	<b>Conductivity &lt; 10x10<sup>6</sup>Ω</b>
<b>Polyester</b>	<b>Stainless Steel conductive scrim</b>	<b>Conductivity &lt; 15 × 10<sup>6</sup> Ω</b>