

Ø mm	Weight kg	Galvanised Steel
80	0.7	0.9
100	0.8	
125	0.8	
140	0.9	
150	0.9	
160	1.4	1.2
180	1.5	
200	1.6	
224	1.8	
250	1.9	
300	3.5	1.5
315	3.7	
350	3.9	
400	4.3	
450	4.8	
500	5.2	
560	5.6	
630	5.8	
710	6.8	

Notes:

- Standard gasket installed in clamp. 9.5 mm gasket in clamp sizes 80 - 160 mm, 12.7 mm gasket in sizes 180-250 mm, 16.67 mm in sizes 300-710 mm.
- Clamps supplied with galvanised bridge pin. Small bridge pin with clamp sizes 80-160 mm, large pin with 180 mm and larger size clamps.



Temperature Rating of Product Components		
° C	Straight Duct	Gasket
70° (intermittent to 90°)	Galvanised Steel	Nitrile
-20°		

Additional Notes
At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C.

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
QF Clip	Galvanised	ASTM A527 with a G-90 rating
Gasket	Nitrile	ASTM D 1056