



Hose made in silicone coated fiberglass with galvanised steel spiral, for suction of fumes and hot air.

SMOOTH SURFACES ***

FLEXIBILITY ****

ABRASION RESISTANCE ****

TEMPERATURE RANGE -85°C +300°C
-121°F +572°F

CHEMICAL RESISTANCE **SILICONE**

CRUSHING RESISTANCE ***

Ø I.D.	Ø I.D.	Ø O.D.	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	g/m	mm	bar	bar	m h2o	m	
	51	55	250	26	1.5	4.5	5	4	
	63	67	290	32	1.3	3.9	5	4	
	70	74	405	35	1.2	3.6	5	4	
	76	80	420	38	1.1	3.3	3.97	4	
	83	87	486	42	1.1	3.3	3.97	4	
	89	93	525	45	1.1	3.3	3.85	4	
	102	106	650	51	1	3	3	4	
	114	119	720	57	0.9	2.7	2.2	4	
	121	126	790	61	0.9	2.7	2	4	
	127	132	800	64	0.8	2.4	1.7	4	
	140	145	925	70	0.7	2.1	1.5	4	
	152	157	980	76	0.7	2.1	1.4	4	
	178	183	1190	89	0.6	1.8	1.1	4	
	203	208	1330	102	0.5	1.5	0.7	4	
	254	259	1650	127	0.4	1.2	0.45	4	
	305	310	2000	153	0.3	0.9	0.3	4	

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.