



# DUST SPARES

dust control spare parts for industry

[www.dustspares.co.uk](http://www.dustspares.co.uk) 08456 800 696

- Minimum Supporting
- Versatility on site
- Slow radius bends
- Simple increase or reductions of size
- Basically smooth bore Mobility
- Jointing of lengths
- Manipulation
- Economy
- Good resistance to many acids/chemicals
- Self-extinguishing



**Description:** Stayput is constructed of a rigid grey PVC strip profile which is spirally wound to produce a robust flexible duct. Supplied in standard 5 metre lengths.

**Applications:** Stayput is self-supporting and can be bent into shape making it ideal for fume extraction from work benches and the removal of woodworking dust to comply with Health and Safety regulations. Other applications include air supply, liquid supply at low pressures, conveyance of powders, granules and dust extraction.

**Sizes:** Stock diameters are 55mm, 75mm, 95mm, 125mm & 150mm. Other diameters from 22mm to 500mm are available subject to minimum order. Stayput diameters can be manipulated up to 35% by twisting the tube clockwise or anti-clockwise.

**Temperature Range:** -20°C to +80°C

| Hose I.D. | Wall Thickness. | Approx. Bend Radius. | Length.  | Weight. |
|-----------|-----------------|----------------------|----------|---------|
| 55mm      | 3mm             | 140mm                | 5 metres | 2.1 Kg  |
| 75mm      | 3mm             | 190mm                | 5 metres | 3.7 Kg  |
| 95mm      | 3mm             | 240mm                | 5 metres | 5.3 Kg  |
| 125mm     | 3mm             | 315mm                | 5 metres | 7.3 Kg  |
| 150mm     | 3mm             | 375mm                | 5 metres | 8.3 Kg  |